

## Claims

1. (Withdrawn) A method of fabricating a plurality of circuit boards for receiving different sets of electrical devices from a plurality of raw boards of the same type, comprising:

5                   forming respective networks of electrically conductive traces with a common layout on said raw boards, said networks each comprising a plurality of open circuits;

                  loading respective pluralities of electrical device receivers on said boards;

10                   loading respective electrical device controllers on said boards; and

                  closing some of said open circuits, such that some of said boards have different patterns of closed circuits and thereby different interconnections between  
15                   their respective receivers and controllers.

2. (Withdrawn) The method of claim 1, wherein said loading of electrical device receivers, said loading of electrical device controllers and said closing open circuits are performed simultaneously.

3. (Withdrawn) The method of claim 1, wherein a common pattern of electrical device receivers is loaded onto each of said boards.

4. (Withdrawn) The method of claim 3, wherein each of said electrical device receivers is configured to receive a first type of electrical device, selected receivers on each board are also configured to receive a second type of  
5                   electrical device, at least one controller on each board is

configured to control said first type of electrical device,  
and at least one controller on each board is configured to  
control said second type of device.

5           5. (Withdrawn) The method of claim 4, further  
comprising loading electrical devices into the receivers of  
each board, with said second type of electrical device  
loaded into all of said selected receivers on some of said  
boards, and said first type of electrical device loaded  
into at least some of said selected receivers on others of  
said boards, wherein selected one of said open circuits are  
closed such that each of said electrical devices on each  
board is controlled through the network of traces on that  
10 board by a correspondingly configured controller.

          6. (Withdrawn) A method of fabricating a plurality of  
circuit boards for receiving different sets of circuit  
cards from a plurality of raw boards of the same type,  
comprising:

5           forming respective networks of electrically  
conductive traces with a common layout on said raw boards,  
each of said networks comprising a common plurality of open  
circuit resistor terminal pairs;

          loading respective pluralities of pin receptacle  
10 arrays and controllers in a common pattern on said boards;  
and

          loading zero ohm resistors across respective  
terminal pairs on at least some of said boards  
simultaneously with the loading of said pin receptacle  
15 arrays and controllers on said at least some boards, such  
that some of said boards have different patterns of zero

ohm resistors, and thereby different interconnections between their respective arrays and controllers.

7. (Withdrawn) The method of claim 6, wherein said pin receptacle arrays are each configured to receive a first type of circuit card, at least some of said arrays on each board are also configured to receive a second type of circuit card, at least one controller on each board is configured to control said first type of circuit cards, and at least one controller on each card is configured to control said second type of circuit card.

8. (Withdrawn) The method of claim 6, wherein at least some of said resistor terminal pairs are left open circuit.

9. (Withdrawn) The method of claim 6, wherein at least some of said resistor terminal pairs are provided between pin receptacle arrays on each board.

10. (Withdrawn) The method of claim 6, wherein at least some of said resistor terminal pairs are provided between controllers and pin receptacle arrays on each board.

11. (Currently Amended) A configurable circuit board, comprising:

a substrate;

a plurality of electrical device receivers on said substrate, at least some of said receivers ~~configured to receive~~ for receiving a selectable one of multiple different electrical devices having different respective interfaces with said receivers;

10           a plurality of controllers on said substrate ~~for~~  
said receivers; and

15           an electrically conductive interconnection  
network on said substrate interconnecting said controllers  
with said receivers, said network comprising sets of zero  
ohm resistor terminals that enable at least some of said  
receivers to be connected to different controllers,  
depending upon a pattern of zero ohm resistors connected  
across said terminals.

12. (Original) The configurable circuit board of claim  
11, wherein the terminals of at least some of said sets are  
separated by open circuits.

13. (Original) The configurable circuit board of claim  
11, further comprising respective zero ohm resistors short  
circuiting the terminals of at least some of said sets.

14. (Original) The configurable circuit board of claim  
13, wherein the terminals of some of said sets are  
separated by open circuits.

15. (Original) The configurable circuit board of claim  
11, said receivers comprising respective arrays of pin  
receptacles.

16. (Original) The configurable circuit board of claim  
15, at least some of said receivers having different  
numbers of pin receptacles.

17. (Original) The configurable circuit board of claim 16, wherein said receivers having different numbers of pin receptacles comprise a common core pin receptacle pattern.

18. (Currently Amended) A The configurable circuit board ~~of claim 11~~, comprising:

a substrate;

5 a plurality of electrical device receivers on said substrate, at least some of said receivers for receiving a selectable one of multiple different electrical devices having different respective interfaces with said receivers;

a plurality of controllers on said substrate; and

10 an electrically conductive interconnection network on said substrate interconnecting said controllers with said receivers, said network comprising sets of zero ohm resistor terminals that enable at least some of said receivers to be connected to different controllers,  
15 depending upon a pattern of zero ohm resistors connected across said terminals, wherein at least some of said sets of zero ohm resistor terminals are connected between different receivers.

19. (Currently Amended) The A configurable circuit board ~~of claim 11~~, comprising:

a substrate;

5 a plurality of electrical device receivers on said substrate, at least some of said receivers for receiving a selectable one of multiple different electrical devices having different respective interfaces with said receivers;

a plurality of controllers on said substrate;

10 and

an electrically conductive interconnection  
network on said substrate interconnecting said controllers  
with said receivers, said network comprising sets of zero  
ohm resistor terminals that enable at least some of said  
15 receivers to be connected to different controllers,  
depending upon a pattern of zero ohm resistors connected  
across said terminals, wherein at least some of said sets  
of zero ohm resistor terminals are connected between  
respective controllers and respective receivers.

20

20. (Original) The configurable circuit board of claim  
11, said circuit board comprising a computer mother board.